



## MOUNTING ISTRUCTIONS

V1.0

Code: **AW0528S**

Name: **DVR enclosure /MINI/VERTICAL**

Metal enclosure for CCTV recorder

**IM528S**



Edition: 2 z from 02.11.2023  
Supersedes edition: 1 from 14.06.2023

### 1. Destination:

Enclosure protects recorder against unauthorized access or theft. Made of 1,2 mm steel plate. Set includes one key (different code), two keys included and tamper switch unwanted enclosure opening.

Due to vertical installation and low depth, it is ideal for places where deeper enclosures or cabinets type RACK 19" cannot be installed.

After opening enclosure, front cover is held in a horizontal position, providing easy access to buttons on front panel of DVR.

Enclosure has a special holder with retaining straps that allows for installation of recorders of following dimensions: width up to 260 mm, height: up to 55 mm, depth up to 250 mm.

### 2. Specifications:

**Table 1. Electrical parameters.**

<b>Tamper switch protection</b>	1 x microswitch: opening of enclosure 0,5 A; 50 V DC max. NC - normally closed contacts optionally: 1 x microswitch: detachment form wall, 0,5A; 50 V DC (required PKAZ067)
<b>Protection class EN 62368-1</b>	I (first)
<b>Rated current of protective connection</b>	6 A max
<b>Declarations, warranty</b>	CE, 2 years

**Table 2. Mechanical parameters.**

<b>External dimensions of enclosure</b>	W=319, H=429, D+D <sub>2</sub> =81+14 [ +/-2 mm]
<b>External dimensions of front panel</b>	W <sub>2</sub> =325, H <sub>2</sub> =433 [ +/-2 mm]
<b>Dimensions of recorder space</b>	W <sub>1</sub> =260, H <sub>1</sub> =250, D <sub>1</sub> =55 [ +/-2 mm]
<b>Material</b>	sheet steel DC01, thickness: 1,2mm corrosion protection Color: RAL 9005 (black matt)
<b>Closing</b>	Lock x 1 pcs (MR008 different code)
<b>Destination</b>	inside
<b>Net/gross weight</b>	5 / 5.2 [kg]
<b>Notes:</b>	distance from wall 14mm set includes one key (different code), two keys included enclosure is fitted with straps for mounting recorder, vertical installation of recorder

**Table 3. Operating parameters.**

<b>Protection grade EN60529</b>	IP20
<b>Operating temperature</b>	-10°C ...+40°C
<b>Storage temperature</b>	-20°C ...+60°C
<b>Relative humidity</b>	20%...90%, without condensation
<b>Sinusoidal vibrations during operation</b>	unacceptable
<b>Impulse waves during operation</b>	
<b>Direct insolation</b>	
<b>Vibrations and impulse waves during transport</b>	PN-83/T-42106




Figure 1. Dimensions.



Figure 2. View of enclosure.



Figure 3. Sample assembly – recorder

**Pulsar sp. j.**

Siedlec 150, 32-744 Łapczyca, Poland

Tel. (+48) 14-610-19-45

e-mail: [sales@pulsar.pl](mailto:sales@pulsar.pl)

http:// [www.pulsar.pl](http://www.pulsar.pl)

