

1. Product description

Enclosure construction is compliant with requirements of General Data Protection Regulation (GDPR), as personal data must be protected and stored securely. Surface mounted enclosure DVR/Monitor/RACK/vertical white protects recorder/monitor/switch against unauthorized access or theft. Made of 1,2 mm steel plate. In enclosure there is installed bracket with stripes for mounting recorder and another bracket for mounting monitor max. 22" (VESA 75x75 / VESA 100x100). Set includes: two locks (different code), two keys/each lock, mounting plate for monitor, RACK brackets - 4U, stripes for mounting recorder, tamper switch indicating enclosure opening, screws (RAS4 - 2pcs, M4x10 - 4 pcs), three pole connector with fuse, screws for mounting power distribution unit.

Additional equipment that can be mounted inside: ARAW45 fan with thermostat and ML572 power distribution unit.

Possibility of install inside:


- Switches PoE – back enclosure / RACK brackets.
- RACK switches of SF series – RACK brackets.
- Recorder – back enclosure - strips / RACK bracket.
- Monitor (max 22") – hinged mounting plate.
- Monitor mounting standard: VESA 75x75 / VESA 100x100
- Batteries.
- Power distribution unit.

Main features:

- Surface mounted construction.
- Removable door (convenient installation of wiring and other equipment).
- Removable mounting plate for monitor.
- RACK brackets – 4U.
- Knock-outs and holes in the back of enclosure.
- Enclosure locked with a key.


2. Technical parameters

External dimensions of enclosure	W=585, H=650, D+D₁=261+14 [-/+2mm]
External dimensions of front panel	W₁=590 H₁=655 [-/+2mm]
Dimensions of recorder space	W₂=480 H₂=400, D₂=180 [-/+2mm]
Hinged mounting plate	W₃=533 H₃=184, D₃=71 [-/+2mm]
Monitor mounting standard	VESA 75x75 / VESA 100x100
Position of RACK 19" profiles	H₄=475 [-/+2mm]
Fitting battery	4x 7Ah
Net/Gross weight	16,7 / 18,0 [kg]
Operation conditions	Temperature: -10°C ÷ +40°C relative humidity 20%...90%, without condensation
Material	DC01 sheet, thickness: 1mm, colour: RAL9003 (white) - anticorrosion protection
Tamper switch protection	1 x microswitch: enclosure opening 0,5 A; 50 V DC max. NC – normally closed contacts Optionally: 1 x microswitch: detachment form wall, 0,5A; 50 V DC (required PKAZ067)
Locking	Lock MR008 (different code) x 2 pc.
Application	Inside
Declarations, warranty	CE, 2 years from production date
Notes	Distance from the wall 14mm RACK brackets – 4U The possibility of mounting ARAW45 fan with sensor Possibility of install monitor.



4. Example of mounting configurations.





Pulsar sp. j.

Siedlec 150, 32-744 Łapczyca, Poland
 Tel. (+48) 14-610-19-40, Fax. (+48) 14-610-19-50
 e-mail: biuro@pulsar.pl, sales@pulsar.pl
 http:// www.pulsar.pl, www.zasilacze.pl