

AWZ 625 v.1.0 PU2/HV Relay module

Edition: 2 from 01.03.2018 Supersedes the edition: 1 from 19.06.2017

EN

1. Intended use.

The PU2/HV (AWZ 625) relay module is to be used in low-voltage installations. It is intended for controlling and status indication in e.g. alarm or access control systems. It may be used to control devices of high power consumption via OC outputs of alarm systems. Moreover, it ensures galvanic isolation of signals, power sources relating to the outputs of the module.

2. Installation.

The module is equipped with a plastic panel with self-adhesive tape that enables fixing it to a flat surface (side panel of an enclosure, a buffer PSU, etc.) and holes for bolting the panel to the mounting surface.

3. Description of the module.

- 3.1 Components.
- 1 input module terminals
- 2 LED (indicates relay's operations)
- 3 relay
- 4 fuse
- 5 relay output terminals

3.2 Connectors.

-I+ inputs of the voltage that control the relay
- I + INDUIS OF THE VOILAGE THAT CONTROL THE RELAV
,

- NC normally closed relay's contact
- NO normally open relay's contact
- C common terminal of the relay





Fig. 1. General view of the module.

5. Electrical diagram



WEEE PARKING

According to the EU WEE Directive – It is required not to dispose of electric or electronic waste as unsorted municipal waste and to collect such WEEE separately.

Pulsar Siedlec 150, 32-744 Łapczyca, Polska Tel. (+48) 14-610-19-40, Fax. (+48) 14-610-19-50 e-mail: <u>biuro@pulsar.pl</u>, <u>sales@pulsar.pl</u> http:// <u>www.pulsar.pl</u>, <u>www.zasilacze.pl</u>

4. Specifications.

Voltage of the relay's coil	10÷16V DC/AC (-/+5%),
Current of the relay's coil	33mA@12VDC
Coil resistance	360 OHM (-/+10%)
Coil power	400mW
Number of relays	2
Voltage of the relay's contacts	30VDC / 250VAC max.
Current of the relay's contacts	6A max.
Contacts of relay	NC/NO/C
ON/OFF time	15ms/8ms (-/+5%)
Operating conditions	2nd environmental class, -10°C÷ 40°C
Enclosure	open-frame design, IP00
Dimensions	L=75, W=70, H=30 [mm, +/-2]
Net/gross weight	0,08 / 0,11 [kg]
Installation	installation tape or installation bolt x2
Declaration, warranty	CE, 2 year from the production date
Notes	Leads on connections: Ø 0,41÷1,63
	(AWG 26-14) 0,2 ÷ 1,5mm ²
	Ø 0,41÷2,59 (AWG 26-10) 0,5 ÷ 4mm ²
	- relay contacts