

CODE: **AWO221** v1.1/III
 NAME: **Casing 17/TRP40/DSPR/S/GRADE 3**



DESTINATION

DSC: (PC 1404, 1616, 1832, 1864,4020) + 5108 (4108, 5208, 5100, 4116)

MODULES: (PC 5204, 5400, 5580, 5200, 4216,4204) + (5108, 5208, 4108, 5100, 4116)

PARADOX: (E55, E65, 728ULT, EVO48, EVO192, SP4000, SP5500, SP6000, SP7000) + ZX 8 (ZX 4, HUB2, PGM4)

RISCO: PRO24 z 17 Ah
 PRO116, 128, 140 z 7Ah

SATEL: CA4V1, CA5, CA6
 (VERSA5, 10, 15, CA10) + CA10E (CA64E, SM, MST1)
 (INTEGRA24, 32) + CA64E (SM)

MODULES: CA64 (PP, EPS, ADR, O-R, O-ROC, O- OC, OPS- OC, OPS- R, OPS- ROC, VGM- 16, SR, PTSA) + CA64E (SM)

PYRONIX: MATRIX 424, 6, 816, 832, 832+

CROW: RUNNER 4,8

TEXECOM: PREMIER 412, 816, 832, 48, 88, 168, 640

TELMOR: TCA- 824 + TEX800

ROGER: PR402, CPR 32-SE

EBS: PX 202A

PULSAR: MS 1012, MSR 1012, MSRK 1012
 MS 2012, MSR 2012, MSRK 2012

TECHNICAL DATA

External dimensions of the enclosure: W=340, H=300, D=110 D_i=15 [+/- 2mm]

External dimensions of the front panel: W_i=335, H_i=400 [+/- 2mm]

Weight net/gross: 4,1kg / 4,4kg [+/-0,1kg]

Battery space: 17 Ah/12 V Sealed Lead Acid (SLA)

Transformer: TRP 40VA/16V/18V in the case of PC/ABC in class UL94-V0, IP20

Power supply ~230 V (-15%/+10%), 50Hz, 200mA (max.)

Power supply output: U1=16 V AC or U2=18 V AC (-5%, +15%), I1=2,2 A or I2=2,0 A (max.)

Operating environment: class II, -10°C+ 40°C

Material description: sheet steel DC01, thickness: 1,0mm, protection anticorrosion, color: RAL 9003

Destination: indoor

Tamper protection: enclosure is equipped with set including mounting bracket with tamper

Closing: screwed x 2

Notes: optional: lockable, distance from wall (mounting surface) - 15mm, "C"-shaped doors and the bottom of the casing, no hinges

Declaration, warranty: CE, RoHS in accordance with the EN50131 standard, Grade 3
 2 year from the production date