



## DESTINATION

Enclosure construction is compliant with requirements of General Data Protection Regulation (GDPR), as personal data must be protected and stored securely.

Enclosure protects recorder against unauthorized access or theft. Made of 1,2 mm steel plate. Set includes two keys (different code) for each lock and a tamper switch indicating enclosure opening or unwanted removal of enclosure from wall.

Due to vertical installation and low depth, it is ideal for places where deeper enclosures or cabinets type RACK 19" cannot be installed.

After opening enclosure, front cover is held in a horizontal position, providing easy access to buttons on front panel of DVR.

Enclosure has a special holder with retaining straps that allows for installation of recorders of following dimensions: width up to 375 mm, height: up to 95 mm, depth up to 335 mm.

External dimensions of enclosure:	W=432, H=501, D+D <sub>2</sub> =121+14 [+/-2 mm]	
Dimensions of recorder space:	W <sub>1</sub> =375, H <sub>1</sub> =335, D <sub>1</sub> =95 [+/- 2mm]	
Net/gross weight:	8,2 / 9 [kg]	
Operating conditions:	-10°C+40°C, relative humidity 20%90%, without condensation	
Material:	sheet steel DC01, thickness: 1,2 mm, corrosion protection, color: RAL 9005 (black matt)	
Destination:	inside	
Tamper switch protection:	2 x microswitch: opening of enclosure 0,5 A; 50 V DC max. NC - normally closed contacts detachment form wall, 0,5A; 50 V DC max. NC – normally closed contacts	
Closing:	Lock x 2 pcs (MR008 different code)	
Notes:	distance from wall 14mm Set includes two keys (different code) for each lock. enclosure is fitted with straps for mounting recorder, vertical installation of recorder	
Declarations, warranty:	CE, 2 years	
el. +48-14-610-19-45 www.pulsar.pl -mail: <u>sales@pulsar.pl</u>	Linkedin Lusarpl	