


HPSB series power supply unit

Buffer, switch mode power supply unit 13,8V DC




CODE: **HPSB 1512B** v.1.0/VII
TYPE: **HPSB 13,8V/1A/7Ah Buffer, switch mode power supply unit**

EN**



GREEN POWER



Features:

- DC 13,8V/1A uninterruptible power supply*
- fitting battery: 7Ah/12V
- wide range of mains supply: 176÷264V
- high efficiency 70%
- battery charging and maintenance control
- excessive discharging (UVP) protection
- battery charge current 0,5A
- battery output full protection against short-circuit and reverse polarity connection
- LED indication
- protections:
 - SCP short-circuit protection
 - OVP overvoltage protection
 - overvoltage protection (input AC) against sabotage
 - overload protection (OLP)
- warranty – 2 year from the production date

DESCRIPTION

A buffer PSU intended for uninterrupted supply to devices that require stabilised voltage of **12V DC (+/-15%)**. The PSU provides voltage of **U=13,8V DC** with output current of **I=1A + 0,5A for battery charging***. In case of power decay, a battery back-up is activated immediately. The PSU is constructed based on the switch mode PSU, with high energy efficiency. The PSU is housed in a metal enclosure (colour RAL 9003) which can accommodate a 7Ah/12V battery. A micro switch indicates door opening (front cover).

During normal operation, the total current drawn by the equipment may not exceed **I = 1 A***.

Maximum battery charging current: **0,5 A***.

Total device current + battery: **1,5 A max***.

* Refer to chart 1

HPSB series power supply unit

Buffer, switch mode power supply unit 13,8V DC



SPECIFICATIONS	
PSU type	A (EPS - External Power Source)
Mains supply	176÷264V AC 50Hz
Current up to	0,35A@230VAC
Supply power	25W max.
Efficiency	70%
Output voltage	13,8V DC – buffer operation 9,5V÷13,8V DC – battery-assisted operation
Output current $t_{AMB}<30^{\circ}C$	1A + 0,5A battery charge- refer to chart 1
Output current $t_{AMB}=40^{\circ}C$	0,7A + 0,5A battery charge - refer to chart 1
Voltage adjustment range	12÷14VDC
Ripple	120mV p-p max.
Battery charge current	0,5A max. @ 7Ah ($\pm 5\%$)
Short-circuit protection SCP	electronic, automatic return
Overload protection OLP	105-150% of the PSU power, automatic return
Battery circuit protection SCP and reverse polarity connection	PTC polymer fuse
Surge protection	varistors
Overvoltage protection OVP	>16V (automatic recovery)
Excessive discharge protection UVP	$U<9,5V (\pm 5\%)$ – disconnect of connection battery
Sabotage protection: - TAMPER output indicating enclosure opening	- microswitch, NC contacts (enclosure closed), 0,5A@50V DC (max.)
LED indication	Yes
Operating conditions	2nd environmental class, $-10^{\circ}C\div+40^{\circ}C$
Enclosure	Steel plate DC01, thickness: 0,8mm, colour: RAL 9003
Dimensions	$W=200$ $H=230$ $D+D_1=82 + 8$ [± 2 mm] $W_1=204$ $H_1=235$ [± 2 mm]
Net/gross weight	1,3 /1,5 kg
Fitting battery	7Ah/12V (SLA) max. 165x90x75mm (WxHxD) max
Closing	Cheese head screw x 1 (at the front), (lock assembly possible)
Declarations, warranty	CE, RoHS, 2 year from the production date
Notes	The enclosure does not adjoin the assembly surface so that cables can be led. Convectional cooling. Connectors: Power-supply: $\Phi 0,63\div 2,5$ Battery output BAT: 6,3F-2,5.




CHART 1. Acceptable output current from the PSU depending on ambient temperature.

HPSB series power supply unit


Buffer, switch mode power supply unit 13,8V DC



Optional configurations:

Buffer power supply unit HPSB 13,8V/2x1A/7Ah.

- HPSB1512B + LB2 2x0,5A (AWZ586) + 7Ah



Buffer power supply unit HPSB 13,8V/5V÷7,4V/1A/7Ah.

- HPSB1512B + DCDC10 (5V÷7,4V/1A) + 7Ah

