

HPSB series power supply unit

Buffer, switch mode power supply unit 27,6V DC



EN**

CODE: **HPSB 3524C** v.1.0/VIII
TYPE: **HPSB 27,6V/3A/2x17Ah Buffer, switch mode power supply unit**

GREEN POWER



Features:

- DC 27,6V/3A uninterruptible power supply*
- fitting battery: 2x17Ah/12V
- wide range of mains supply: 176÷264V
- high efficiency 83%
- battery charging and maintenance control
- excessive discharging (UVP) protection
- jumper selectable battery charge current 0,5A/1A
- battery output full protection against short-circuit and reverse polarity connection
- LED indication
- protections:
 - SCP short-circuit protection
 - OVP overvoltage protection
 - overvoltage protection (AC input)
 - against sabotage
 - overload protection (OLP)
- warranty – 2 year from the production date

DESCRIPTION

A buffer PSU is intended for an uninterrupted supply to devices requiring stabilised voltage of **24V DC (+/-15%)**. The PSU provides voltage of **U=27,6V DC**. Current efficiency:

1. Output current 3A + 0,5A battery charge*
2. Output current 2,5A + 1A battery charge*

Total device current + battery: 3,5A max*.

In case of power decay, a battery back-up is activated immediately. The PSU is constructed based on the switch mode PSU, with high energy efficiency. The PSU is housed in a metal enclosure (colour RAL 9003) which can accommodate two 17Ah/12V batteries. A micro switch indicates door opening (front cover).

* Refer to chart 1

HPSB series power supply unit

Buffer, switch mode power supply unit 27,6V DC



SPECIFICATIONS	
PSU type	A (EPS - External Power Source)
Mains supply	176÷264V AC 50÷60Hz
Current up to	0,9A@230VAC
Supply power	100W max.
Efficiency	83%
Output voltage	27,6V DC – buffer operation 19V÷27,6V DC – battery-assisted operation
Output current $t_{AMB}<30^{\circ}\text{C}$	3A + 0,5A battery charge - refer to chart 1 2,5A + 1A battery charge - refer to chart 1
Output current $t_{AMB}=40^{\circ}\text{C}$	2A + 0,5A battery charge - refer to chart 1 1,5A + 1A battery charge - refer to chart 1
Voltage adjustment range	24÷28VDC
Ripple	150mV p-p max.
Battery charge current	0,5A / 1A max. @ 2x17Ah ($\pm 5\%$) – jumper selectable
Short-circuit protection SCP	electronic, automatic return
Overload protection OLP	105-150% of the PSU power, automatic return
Battery circuit protection SCP and reverse polarity connection	PTC polymer fuse
Surge protection	varistors
Overvoltage protection OVP	>32V (automatic recovery)
Excessive discharge protection UVP	U<19V ($\pm 5\%$) – disconnect of connection battery
Sabotage protection: - TAMPER output indicating enclosure opening	- microswitch, NC contacts (enclosure closed), 0,5A@50V DC (max.)
LED indication	Yes
Operating conditions	2nd environmental class, $-10^{\circ}\text{C}\div 40^{\circ}\text{C}$
Enclosure	Steel plate DC01, thickness: 0,7mm, colour: RAL 9003
Dimensions	W=400 H=350 D+D ₁ =92 + 8 [+/- 2mm] W ₁ =405 H ₁ =355 [+/- 2mm]
Net/gross weight	3,8 / 4,1 kg
Fitting battery	2x17Ah/12V (SLA) max. 360 x 170 x 85mm (WxHxD) max
Closing	Cheese head screw x 2 (at the front), (lock assembly possible)
Declarations, warranty	CE, RoHS, 2 year from the production date
Notes	The enclosure does not adjoin the assembly surface so that cables can be led. Convectional cooling. Connectors: Power-supply: $\Phi 0,63\div 2,5$ Battery output BAT: 6,3F-2,5.




CHART 1. Acceptable output current from the PSU depending on ambient temperature.

HPSB series power supply unit


Buffer, switch mode power supply unit 27,6V DC



Optional configurations:


Buffer power supply unit HPSB 27,6V/8x0,3A/2x17Ah.

- HPSB3524C + LB 8x0,3A (AWZ577 or AWZ580) + 2x17Ah




Buffer power supply unit HPSB 27,6V/3x1A/2x17Ah.

- HPSB3524C + LB4 3x1A (AWZ575 or AWZ576) + 2x17Ah




Buffer power supply unit HPSB 27,6V/6x0,5A/2x17Ah.

- HPSB3524C + LB8 6x0,5A (AWZ578 or AWZ580) + 2x17Ah




Buffer power supply unit HPSB 27,6V/24V/2,5A/2x17Ah.

- HPSB3524C + RN25024 (27,6V/24V) + 2x17Ah




Buffer power supply unit HPSB 27,6V/24V/5x0,5A/2x17Ah.

- HPSB3524C + RN25024 (27,6V/24V) + LB8 5x0,5A (AWZ578 or AWZ580) + 2x17Ah



Buffer power supply unit HPSB 27,6V/24V/8x0,3A/2x17Ah.

- HPSB3524C + RN25024 (27,6V/24V) + LB8 8x0,3A (AWZ577 or AWZ580) + 2x17Ah



HPSB series power supply unit


Buffer, switch mode power supply unit 27,6V DC



Optional configurations:

Buffer power supply unit HPSB 27,6V/2x5V±18V/2x2A ÷1,3A/2x17Ah.

- HPSB3524C + 2xDCDC20 (2x5V±18V/2A÷1,3A) + 2x17Ah



Buffer power supply unit HPSB 27,6V/2x5V±18V/2x2A ÷1,3A/8x0,5A/2x17Ah.

- HPSB3524C + 2xDCDC20 (2x5V±18V/2A÷1,3A)
+ 2xLB4 8x0,5A (AWZ574 or AWZ576) + 2x17Ah

