


CODE: **PU-NC200** v1.0/I  
 NAME: **Twisted pair wire, U/UTP, cat 5e, 25AWG, Cu, Eca, 305m (indoor)**

EN

**U/UTP**

## DESTINATION

PU-NC200 cable is twisted pair U / UTP, category 5e cable. It can be used for data transmission and power transmission (PoE). It can be used in many systems, i.e. ICT systems, IP video monitoring systems (especially recommended for IP PoE systems), but it will also work well in HD digital closed-circuit television systems (CVI, TVI, AHD). Cable is intended for professional installations inside buildings and complies with the PN-EN 50575 (CPR) standard

## TECHNICAL DATA

Type of cable:	Twisted pair wire
Shield type / Shielding:	U/UTP (unshielded cable)
Category:	5e
Outside diameter of wire / core:	4,5mm / 0,45mm (AWG25)
Coating/core material:	PVC (polwinit) / Cu (99,99%)
Coating colour:	light grey - RAL7035
Reaction to fire class:	Eca
Destination:	indoor
Operating temperature:	20°C+70°C
Laying temperature:	0°C+50°C
Bending radius:	40mm
Cable length in package:	305m
Type / dimensions of packaging:	Cardboard / 345 x 190 x 345 [+/- 2mm]
Net / gross weight:	7,25 / 7,95 [kg]
Declaration, warranty:	CE, CPR, DoP, 5 years
Notes:	marker on cable every 1m