



	<b>WP</b> v1.1/VI el of two fans for RACK	cabinets of	the RS /	ZRS typ	EN*
				/	
			RACK 19" cabinet depth:		
The possibility of cas	cade connection of fans		600mm	800mm	1000mm
		1x RAWP	$\checkmark$	$\checkmark$	$\checkmark$
		2x RAWP	$\checkmark$	$\checkmark$	$\checkmark$
		3x RAWP		$\checkmark$	$\checkmark$
DESTINATION					<u> </u>
	ed in the top plate of RACK cabinet. It force ludes a detachable 230VAC wire.	es air circulation insid	le the cabinet.	It is mounted	outside of
TECHNICAL DATA Mounting dimensions:	W1=285, H1=65 [mm, +/-2]				
Dimensions:	W=298, H=150, D=47 [mm, +/	-2]			
Rated voltage:	220÷240V AC / 50/60Hz	-			

Dimensions:	W=298, H=150, D=47 [mm, +/-2]		
Rated voltage:	220÷240V AC / 50/60Hz		
Rated current:	0,10A+0,12A		
Net/gross weight:	1,56 / 1,64 [kg]		
Materials:	- 1,2mm cold rolled steel sheet (SPCC), color RAL 9004 - two 230VAC fans with a capacity of 2 x 50÷110CBM/H		
Destination:	inside		
Declarations, warranty:	CE, 1 year from production date		
Notes:	- mounting to the top plate of RACK cabinet - possibility of cascade connection of fans - 230VAC LZ=2m wire		

## Mounting to the top plate of RACK cabinet









End caps

Removed caps

Mounted fan