


CODE: **RS108** v.1.4/V
 TYPE: **RS108 10-port switch with power supply for 8 IP cameras, RACK**



Features:

- Switch 10 ports
8 PoE ports 10/100Mb/s (data transfer and power supply)
2 ports 10/100Mb/s (UP LINK)
- **Long Range** mode (up to 250m)
- 30 W for each PoE port, supports devices compliant with the IEEE802.3af/at (**PoE+**) standard
- Supports auto-learning and auto-aging of MAC addresses (1K size)
- LED indication
- Metal enclosure RACK 19" 1U
- color black RAL 9005
- warranty – 2 year from the production date

DESCRIPTION

The RS108 is a 10-ports switch in a RACK 19" metal housing with integrated power supply. Automatic detection of any devices powered in the PoE/PoE+ standard is enabled at the 1 – 8 ports of the switch. The UP LINK ports is used for connection of another network device via RJ45 connector. The LEDs at the front panel indicate the operation status.

The PoE technology ensures a network connection and reduces installation costs by eliminating the need to supply a separate power cable for each device. This method allows supplying other network devices, such as IP phone, wireless access point or router.

TECHNICAL PARAMETERS

Ports	10 10/100Mb/s ports (8 x PoE + 2 x UP LINK) with connection speed auto-negotiation and MDI/MDIX Auto Cross
PoE power supply	IEEE 802.3af/at (1+8 ports), 52 V DC / 30 W at each port *
Long Range mode	Long Range, VLAN
Protocols, Standards	IEEE802.3, 802.3u, 802.3x CSMA/CD, TCP/IP
Bandwidth	1,6Gbps
Transmission method	Store-and-Forward
Optical indication of operation	Switch power supply; Link/Act; PoE Status
Power supply	~100-240 V; 50/60Hz; 1,5 A
Operating conditions	temperature -10°C ÷ 40°C, relative humidity 5% - 90%, no condensation
Mounting dimensions	W=19" H=1U D=227
Dimensions	W=482 W ₁ =440 H=44 D=227 [±2mm]
Additional equipment	RACK 19" 1U, Steel plate, DC01 1,0mm color RAL 9005
Net/gross weight	2,6/2,8 kg
Protection class EN 60950-1:2007	II (second)
Storage temperatur	-20°C ÷ 60°C
Declarations, warranty	CE, 2 year from the production date

* The given value of 30 W per port is the maximum value. The total power consumption should not exceed 96 W.

Connection schemes

